

# Specifications in brief

<b>Type</b>	Digital still camera
<b>Storage media</b>	CF card
<b>Data compression mode</b>	SUPER FINE (10 frames at 4 MB) FINE (20 frames at 4 MB) ECONOMY (50 frames at 4 MB)
<b>Data compression/expansion</b>	Conforming to JPEG
<b>Image format</b>	Exif
<b>Erase mode</b>	Frame/whole/formatting
<b>Lens</b>	Fixed focal length, $f = 6.0 \text{ mm}^*$ , $F = 2.8$ . (* Equivalent to 39 mm for 35 mm camera)
<b>Object distance</b>	0.2 m to $\infty$ (Close-up mode: 0.2 m to 0.8 m) (Usual object distance: 0.8 m to $\infty$ )
<b>Focus control</b>	All range automatic focusing by focal plane automatic focusing
<b>Viewfinder</b>	Real image type
<b>Pickup device</b>	1/3", 1,080,000-pixels CCD
<b>Exposure control</b>	Program AE (EV 6 to 16)
<b>Diaphragm mechanism</b>	Two diaphragm blades driven by step motor (F2.8, F5.6, F11) Shutter speed: 1/8 to 1/500 sec
<b>Photometric system</b>	Multi-photometry, automatic back-light control
<b>Flash</b>	Built-in automatic flashlight, effective distance: 0.5 to 3.0 m, 5800 K Red-eye reduction/AUTO/ON/OFF mode selective

<b>White balance</b>	Focal plane automatic white balance
<b>Shooting mode</b>	Normal, self-timer (10 sec), close-up, 4-frame continuous shooting, digital 2x zoom
<b>Automatic dating</b>	Automatic recording of year-month-day or hour-minute-second
<b>LED's</b>	Card access warning LED, self-timer LED, viewfinder LED's
<b>Buzzer</b>	Various alarms
<b>Power source</b>	AA-size (UM-3) alkaline battery (four), Ni-Cd alkaline battery, Ni-H battery, or exclusive AC adaptor
<b>Battery life</b> (in case of alkaline battery)	1) Preview shooting mode: for 100 shots or more (based on our test conditions) 2) Playback mode: 80 minutes approx. (based on our test conditions)
<b>Working temperature</b>	0°C to 45°C (at humidity of 20% to 95% RH)
<b>PC interface</b>	RS232C serial interface (115.2 kbps)
<b>LCD monitor</b>	1.8-inch color LCD
<b>Playback mode</b>	Still, double zoom-in, index, slide show
<b>Video output</b>	NTSC/PAL (switchable)
<b>Accessories supplied with camera</b>	CF card (4 MB), AA-size alkaline batteries (four), strap, soft case, video output cord, instruction manual (this book), warranty, installation manual, interface cable for IBM PC/AT compatible, interface cable for Macintosh, CD-ROM
<b>Optional accessories</b>	Personal computer connector kit, AC adaptor
<b>Size</b>	119.0 (W) x 76.0 (H) x 50.7 (D) mm
<b>Weight</b>	290 g approx. (excluding batteries, CF card)