## TECHNICAL DETAILS



**Image Sensor:** 1/3 inch CCD, 350,000 pixels (330,000

effective pixels), square pixels, full frame

transfer, suited for VGA display

Recording Media: SmartMedia™

(SSFDC image memory cards)

File Format: EXIF (Exchangeable Image File Format)

Compression: JPEG

**Storage Capacity:** 2MB SmartMedia<sup>™</sup> cards (standard accessory):

Fine mode - approx. 16 Standard mode - approx. 40

**LENS** 

**RECORDING** 

**Construction:** 7 groups, 9 elements, 4 component zoom

with macro

Focal Length: 4.8 - 13mm

(35mm film format equivalent 34 - 92mm)

**Aperture:** f/5 - 5.6 **Focusing:** Fixed Focus **Zoom:** Manual zoom

Remote Operation: Possible with standard accessory cable

**EXPOSURE** 

**Control:** Auto-exposure with CCD variable

charge time electronic shutter (fixed aperture)

Shutter Speed: 1/30 to 1/10,000 second

Metering: TTL center-weight metering in CCD

Sensitivity: ISO 160 or equivalent

Flash mode: Auto-flash, Manual fill-flash, Flash Cancel

Flash control: Flash sensor - silicon photocell

**LCD MONITOR** 

**Type:** 1.8 inch color LCD (liquid crystal display)

Pixels: 71,760 pixels

**OTHER** 

White Balance: Automatic

Interface: Digital in/out (Mini Din 8 pin, serial)

Power: AA Nicad or Alkaline batteries

AC Adapter AC-V1 (sold separately)

(DC terminal on camera body)

**Dimensions:** 131 x 71.5 x 37mm (WxHxD)

5.2 x 2.8 x 1.5 in (WxHxD)

Weight: 250g (8.8 oz.) approximately

(not including battery and SmartMedia™)

Specifications are based on the latest information available at the time of printing and are subject to change without notice.

When installing Adobe® PhotoDeluxe®, included in this package, use the serial number below.

HJW100T7200005-328